

Multi Type Air Conditioner **OWNER'S MANUAL**

MODELS: 6710 YS 6720 YS

IMPORTANT

Please read through this manual. It contains valuable information about your air conditioner. This manual may help save time and money by explaining proper product maintenance and preventing improper use.

PRECAUTIONS

Pay close attention to precautions in order to prevent potential hazards and damage from misuse or improper installation. LG is not responsible for any damages caused by misuse of the product.

Prior to installation, this air-conditioning unit must be submitted for approval by the utility service which provides electricity (EN 61000-3 Norm.)

TABLE OF CONTENTS

1. Safety Precautions

2. Operating Instructions

- a. Preparation before operation
- b. Remote Control Features
- c. Operation Mode Selection
- d. Additional features

3. Care and Maintenance

4. Troubleshooting Tips Before You Call For Service

F or Your Records

Write the model and serial numbers here:

Model

Serial #

You can find them on a label on the side of each unit.

Dealer's Name

Date Purchased

Read This Manual

Inside you will find many helpful hints on how to use and maintain your air conditioner properly. Just a little preventive care on your part can save you a great deal of time and money over the life of your air conditioner.

You'll find many answers to common problems in the chart of troubleshooting tips. If you review our chart of

Troubleshooting Tips first, you may not need to call for service at all.



- Contact the authorized service technician for repair or maintenance of this unit.
- Contact the installer for installation of this unit.
- The air conditioner is not intended for use by young children or invalids without supervision.
- Young children should be supervised to ensure that they do not play with the air conditioner.
- When the power cord is to be replaced, replacement work shall be performed by authorized personnel only.
- Installation work must be performed in accordance with the national wiring standards by authorized personnel only.





Precautions

To prevent injury and property damage, follow these instructions.


▲ Incorrect operation due to ignoring instructions will cause harm or damage, the seriousness of which is indicated by the following symbols.

 MARNING
 This symbol shows the possibility of death or serious injury.

 CAUTION
 This symbol indicates the possibility of injury or damage to property.




■ The following items are classified by these symblos.



∍ 🗥 CAUTION →


- Contact the authorized Service technician for repair or maintenance of this unit.
- Contact the installer for installation of this unit.
- The air conditioner is not intended for use by young children or infirm persons without supervision.
- Young children should be supervised to ensure that they do not play with the air conditioner.



Preparation before operation

How to Insert the Batteries

- Remove the battery cover by pulling it according to the arrow direction.
- 2 Insert new batteries making sure that the (+) and (-) of battery are installed correctly.
- 3) Reattach the cover by sliding it back into position.




NOTES:


• Use 2 AAA(1.5volt) batteries. Do not use rechargeable batteries.

Storage and Tips For Using the Remote Control

• The remote control may be stored mounted on a wall.



• To operate the room air conditioner, aim the remote control at the signal receptor.




Signal Receptor

Receives the signals from the remote control. (Signal receiving sound: two short beeps or one long beep.)

Operation Indication Lamps

\bigcirc	On/Off	: Lights up during the system operation.
ふ	Sleep Mode	: Lights up during Sleep Mode Auto operation.
╚	Timer	: Lights up during Timer operation.
× ô	Defrost Mode	: Lights up during Defrost Mode or Hot Start operation (Heat pump model only)
OUT DOOR		: Lights up during outdoor unit operation. (Cooling model only)




Operating Instructions

About the remote control on the system

The remote control transmits the signals to the system.

Features of the Remote Control



Healthy Dehumidification Operation

Heating Operation

Cooling Model(√), Heat Pump Model(↓)


₽

START/STOP BUTTON 1) Operation starts when this button is pressed and stops when the button is pressed again. **OPERATION MODE SELECTION BUTTON** Used to select the operation mode. ROOM TEMPERATURE SETTING BUTTONS Used to select the room temperature. INDOOR FAN SPEED SELECTOR Used to select fan speed in four steps low, medium, high, or CHAOS. JET COOL 5) Used to start or stop the speed cooling. (Speed cooling operates super high fan speed in cooling mode.) CHAOS SWING BUTTON 6) Used to stop or start louver movement and set the desired up/down airflow direction. **ON/OFF TIMER BUTTONS** Used to set the time of starting and stopping operation. TIME SETTING BUTTONS Used to adjust the time. (See page 13) TIMER SET/CANCEL BUTTONS Used to set the timer when the desired time is obtained and to cancel the Timer operation. (See page 13) 10) SLEEP MODE AUTO BUTTON Used to set Sleep Mode Auto operation. (See page 13) 11) AIR CIRCULATION BUTTON Used to circulate the room air without cooling or heating (turns indoor fan on/off). (See page 14) 12) ROOM TEMPERATURE CHECKING BUTTON Used to check the room temperature. PLASMA(OPTIONAL) 13) Used to start or stop the plasma-purification function. (See page 12) RESET BUTTON Used prior to resetting time or after replacing batteries.

 \wedge

-À-

How to use the Operation Mode Selection button




Natural wind by the CHAOS logic

Operating


Instructions

□ For more fresh feeling than other fan speed, press the Indoor Fan Speed Selector and set to CHAOS mode. In this mode, the wind blows like natural breeze by automatically changing fan speed according to the CHAOS logic.



DURING AUTO OPERATION:

- □ You cannot switch the indoor fan speed. It has already been set by the Fuzzy rule.
- □ If the system is not operating as desired, manually switch to another mode. The system will not automatically switch from the cooling mode to the heating mode, or from heating to cooling, it must be done by manually resetting.
- □ During Auto Operation, pressing the chaos swing button makes the horizontal louvers swing up and down automatically. If you want to stop auto-swing, press the chaos swing button again.




DURING HEALTHY DEHUMIDIFICATION OPERATION:

□ If you select the dehumidification mode on the operation selection button, the A/C starts to run the dehumidification function, automatically setting the room temp. and airflow volume to the best condition for dehumidification based on the sensed current room temp.


In this case, however, the setting temp. is not displayed in the remote control and you are not able to control the room temp. either.

□ During the healthy dehumidification function, the airflow volume is automatically set according to the optimization algorithm responding to the current room temp. status and makes the room condition healthy and comfortable even in the high humidity season.




NATURAL WIND BY THE CHAOS LOGIC


□ For more fresh feeling than other fan speed, press the Indoor Fan Speed Selector and set to CHAOS mode. In this mode, the wind blows like natural breeze by automatically changing fan speed according to the CHAOS logic.



NOTE:

- □ During the JET COOL function at any moment, the A/C starts to blow the cool air at extremely high speed for 30 minutes setting the room temp. automatically to 18°C. It is especially used to cool the room temp. in the shortest time in a hot summer.
- In heat pump mode or neuro fuzzy mode however, the JET COOL function is not available.
- □ In order to return to the normal cooling mode from the JET COOL mode, you just press either the operation mode selection button, airflow volume selection or temp. setting button or the JET COOL button again.






Operating Instructions

Additional features

Sleep Mode





The Timer is programmed in one-hour increments by pressing the Sleep Mode Auto button 1 to 7 times.

The sleep mode is available for 1 to 7 times. To alter the time period in steps of 1 hour, press the Sleep Mode Button while aiming at air conditioner.



Make sure the Sleep Mode Auto LED lights up.

Setting the Time

Time can be set only when you have pressed the Reset button. If you have just replaced the batteries, the Reset button should be pressed to reset the time.

Press the Start/Stop button.



To cancel the Sleep Mode, press the sleep Mode Auto button several times until the star $(\stackrel{\frown}{\not\curvearrowright})$ disappears from the operation display.

Note: The Sleep Mode will be operated at low fan speed (cooling) or medium fan speed (heat pump only) for quiet sleeping.

IN COOLING MODE: The temperature will automatically rise by 1°C over the next 30 minutes and by 2°C in 1 hour for comfortable sleeping.



Press the Time Setting buttons until the desired time is set.

3:30



Press the Timer SET button.

Note: Check the indicator for A.M. and P.M.

Delay Start/Pre-Set Stop



Make sure the time is set correctly on the remote control display.

Press the ON/OFF Timer buttons to turn Timer on or off.



Press the Time Setting buttons until the desired time is set.

OFF TIME

am 12:00

Delay OFF Timer




Delay ON Timer

Press the selected on/off setting by pressing the Timer SET button while aiming the remote control at the signal receptor.

SET (

To cancel the setting the timer.

Press the Timer Cancel button while




(The timer lamp on the air conditioner and the display will go out.)

NOTE: Select one of the following four types of operation.

ON TIME

···· 6:00





Delay OFFand ON Timer

Delay ONand OFF Timer

Vertical Airflow Direction Control

The up/down airflow (Vertical Airflow) can be adjusted by using the remote control.



Press the Start/Stop button to start the unit.

Open the door on the remote control.

Press Chaos Swing button and the louvers will swing up and down. Press the Chaos Swing button again to set the vertical louver at the desired airflow direction.

Note:

- □ If you press the CHAOS swing button, the horizontal airflow direction is changed automatically based on the CHAOS algorithm to distribute the air in the room evenly and at the same time to make the human body feel most comfortable, as if enjoying a natural breeze.
- Always use the remote control to adjust the up/down airflow direction. Manually moving the vertical airflow direction louver by hand could damage the air conditioner.
- □ When the unit is shut off, the up/down airflow direction louver will close the air outlet vent of the system.

To adjust left/right(Horizontal Airflow) direction

Caution : Ensure unit is turned off before adjusting the horizontal airflow direction control. Carefully open vertical louver to allow access to the horizontal airflow direction.

Adjust the left/right airflow direction by hand.



Air Circulation Mode


Circulates the room air without cooling or heating.



Press the Start/Stop button. the unit will respond with a beep.

Open the door on the remote control. Press the Air Circulation button. Close the door on the remote control. Now each time that you press the Indoor Fan Speed Selector, the fan speed is shifted from low to CHAOS and back to low again.





Note:


CHAOS Air economizes power consumption and prevents overcooling. The fan speed is automatically changed from high to low or vice versa, depending on the ambient temperature.

Slide Switch Operation

FORCED OPERATION

Operation procedures when the remote control can't be used.

Open the front panel upward and move the Slide Switch to the Forced Operation position. If you want to stop operation, move the Slide Switch to the Auto Restart or the Remote Control position. In case the power comes on again after power failure on the Forced Operation position, the operating conditions are automatically set as follows: During Forced Operation, the initial mode continues.




	Cooling Model	Heat pump Model		
	Cooling Model	Room Temp. \geq 24°C	21°C ≤ Room Temp. < 24°C	Room Temp. < 21°C
Operating mode	Cooling	Cooling	Healthy Dehumidification	Heating
Indoor FAN Speed	High	High	Healthy Dehumidification Rule	High
Setting Temperature	22°C	22°C	23°C	24°C

Auto restart

In case the power comes on again after a power failure, Auto Restarting Operation is the function to operate procedures automatically to the previous operating conditions.

If you want to use this operation, Open the front panel upward and move the slide switch to the Auto Restart position.

If you do not want to use this operation, move the Slide Switch to the Remote Control position.



When you are out for a while, put the Slide Switch on the Remote Control.

HELPFUL INFORMATION

Fan speed and cooling capacity. The cooling capacity indicated in the specification is the value when the fan speed is set to high, and the capacity will be lower at low or medium fan speed.

High fan speed is recommended when you wish to cool the room quickly.



CAUTION: Before performing any maintenance, turn off the main power to the system.


Indoor Unit

Grille, Case, and Remote Control

□ Turn the system off before cleaning. To clean, wipe with a soft, dry cloth. Do not use bleach or abrasives.

NOTE:

Supply power must be disconnected before cleaning the indoor unit.



Air inlet vent Air outlet vent Ohir filters Vertical louver Horizontal louver


AIR FILTERS

The air filters behind the front grille should be checked and cleaned once every 2 weeks or more often if neccessary.



PLASMA FILTER, DEODORIZER FILTER(OPTIONAL)

The PLASMA filter behind the air filters should be checked and cleaned once in every 3 months or more often if necessary.




Don't touch this PLASMA Filter within 10 seconds after opening the inlet grille, it may cause an electric shock.

- □ Never use any of the followings:
 - Water hotter than 40°C Could cause deformation and/or discoloration.
 - Volatile substances Could damage the surfaces of the air conditioner.



- Lift the front access panel and pull the filter tab slightly forward to remove the filter.
- Clean the filter with a vacuum or warm, soapy water.
 - If dirt is conspicuous, wash with a solution of detergent in lukewarm water.
 - If hot water (40°C or more) is used, it may be deformed.

After washing with water, dry well in the shade.




- After removing the air filters, pull slightly forward to remove the PLASMA filter.
- Dip the PLASMA filter into the water mixed with neutral detergent, for 20~30 minutes.
- Dry the PLASMA filter in the shade for a day (Especially, the humidity must be removed perfectly on this parts).
- (1) Note the cuts of electric discharge lines.
- 5 Re-install the PLASMA filter to the original position.




- After removing the air filters, pull slightly forward to remove the DEODORIZER filter.
- 2) Dry in the sunlight for two hours.
- Re-install the DEODORIZER filter to the original position.


Replacement of Purifying Filter(Option)

- Recomended use period : About 2 years
- Open front panel and remove air filters.



2) Remove air purifying filters.






Outdoor Unit


The heat exchanger coils and panel vents of the outdoor unit should be checked regularly. If clogged with dirt or soot, the heat exchanger and panel vents may be professionally steam cleaned.


NOTE:

Dirty or clogged coils will reduce the operating efficiency of the system and cause higher operating costs.



When the air conditioner is not going to be used for a long time.





Operation Tips

Do not overcool the room.	Keep blinds or curtains closed.	Keep the room temperature uniform.
This is not good for the health and wastes electricity.	Do not let direct sunshine enter the room when the air conditioner is in operation.	Adjust the vertical and horizontal airflow direction to ensure a uniform temperature in the room.
Make sure that the doors and windows are shut tight.	Clean the air filter regularly.	Ventilate the room occasionally.
Avoid opening doors and windows as much as possible to keep the cool air in the room.	Blockages in the air filter reduce the airflow and lower cooling and dehumidifying effects. Clean at least once every two weeks.	Since windows are kept closed, it is a good idea to open them and ventilate the room now and then.

Troubleshooting Tips! Save time and money!

Check the following points before requesting repairs or service.... If the fault persists, please contact your dealer or service center.

Case	Explanation	See page
The air conditioner does not operate.	 Have you made a mistake in timer operation? Has the fuse blown or has the circuit breaker been tripped? 	13 -
The room has a peculiar odor.	Check that this is not a damp smell exuded by the walls, carpet, furniture, or cloth items in the room.	
It seems that condensation is leaking from the air conditioner.	Condensation occurs when the airflow from the air conditioner cools the warm room air.	-
Air conditioner does not operate for about 3 minutes when restarted.	This is the protector of the mechanism. Wait about three minutes and operation will begin.	-
Does not cool or heat effectively.	Is the air filter dirty? See air filter cleaning instructions.	16
	Has the temperature been set incorrectly? Are the indoor unit's air inlet or outlet vents obstructed?	7, 10
The air conditioner operation is noisy.	 For a noise that sounds like water flowing. This is the sound of freon flowing inside the air conditioner unit. For a noise that sounds like the compressed air releasing into atmosphere. This is the sound of the dehumidifying water being processed inside the air conditioning unit. 	-
Remote control display is faint, or no display at all.	 Are the batteries depleted? Are the batteries inserted in the opposite (+) and (-) directions? 	5
Crack sound is heard.	• This sound is generated by the expansion/constriction of the front panel, etc. due to changes of temperature.	-

NOTE

WATER RESISTANT: The outdoor side of this appliance is WATER RESISTANT.

The indoor side is not water resistant and should not be exposed to excess water.